

A wood cellulose fiber mulch manufactured from clean recycled newspaper creating an environmental friendly media for all types of erosion control and planting projects. The surface area of the paper allows for even product distribution while creating a stabile matrix for protected seed growth. NaturesOwn mulch works best with NaturesOwn Triple Tac Tackifier, which is a leading tackifier in the industry.



**NaturesOwn**  
We've Got You Covered

**ADVANTAGES**

- Works in all hydro-seeding equipment
- Gives you 20% more loading capacity than wood mulch
- Fast to load from easy to handle bales
- Mixes easily with water and virtually eliminates clogs or plugging
- Flows smoothly and gives you uniform distribution

**APPLICATIONS**

- Hydro-Seeding
- Strawtacking

**TYPICAL PROJECTS**

- Highways
- Golf Courses
- Reclamation
- Residential and Commercial Landscaping

**product specifications**

Packaging: 50 lb bales

Shipment: 2250 lb pallet

Typical Application Rate:	Hydro-Seeding:	
	Mod. to 3:1	1500 lb/acre
	3:1 to 2:1	2000 lb/acre
	Greater than 2:1	2500 lb/acre
	Strawtacking:	
	750 lb/acre	

**PHYSICAL PROPERTIES**

- Water Holding Capacity >1000%
- Moisture Content 12% +/- 3
- Organic Matter >93%
- Ash Content <7%
- pH Range 6.9 +/- 2

Distributed by:



Hamilton Manufacturing Co., Inc.  
901 Russet Street, Twin Falls, Idaho 83301 USA  
208-733-9689 Fax 208-733-9447 E-mail info@hmi-mfg.com  
<http://www.hmi-mfg.com/>

Printed on recycled stock



Call us at 208-733-9689 (US Customers)  
Ask about our hydro-seeding equipment and our product guarantee



**NaturesOwn**  
We've Got You Covered

APPLICATION RATES *50 lb bags*

SLOPE	RECOMMENDED RATE	TANK SIZE	MULCH		COVERAGE			
		gal/liters	lbs	no. of bags	acres	hectares	ft <sup>2</sup>	m <sup>2</sup>
Moderate to 3:1 slope	1500 lbs per acre or 30 bags per acre	3000/11355.6	1500	30	1.00	0.4	43560	3920
		2500/9463	1250	25	0.83	0.33	36300	3267
		1000/3785.2	500	10	0.33	0.13	14520	1307
		500/1892.6	250	5				
3:1 to 2:1 slope	2000 lbs per acre or 40 bags per acre	3000/11355.6	1500	30	0.75	0.3	32670	2940
		2500/9463	1250	25	0.63	0.25	27225	2450
		1000/3785.2	500	10	0.25	0.05	10890	980
		500/1892.6	250	5	0.13	0.01	5445	490
Greater than 2:1 slope	2500 lbs per acre or 50 bags per acre	3000/11355.6	1500	30	0.6	0.24	26130	2352
		2500/9463	1250	25	0.5	0.2	21775	1960
		1000/3785.2	500	10	0.2	0.08	8710	784
		500/1892.6	250	5	0.1	0.04	4355	392

MULCH MIXING RATIO

Mixing Ratio for NaturesOwn Mulch (50 lb bags): 2 parts water: 1 part Mulch

Example:

100 gallons water: 1 (one) 50 lb bag NaturesOwn Mulch  
700 gallons water: 7 (seven) 50 lb bags NaturesOwn Mulch

MIXING INSTRUCTIONS

After the tank is 1/3 full of water add seed and amendments; mix well. Continue filling tank with water and add mulch; mix well. If using compost stop adding water 2/3 full and then mix compost. Finish by filling with water.



Printed on recycled stock

